

??????? ??????? ??? ???????????????? ?????????? Wireguard

Заметка:

- Скрипт добавляется по пути в меню **System - Scripts** с именем **wg-antidpi**, т.е. можно пнуть скрипт когда угодно
- Сам прописывается в **System - Scheduler** при первом ручном запуске

```
# wg-antipdi traffic flood | by antifilter tg chat
# Enable traffic-gen: /system device-mode update traffic-gen=yes

# SCHEDULER
# warn if schedule does not exist and create it
:local scheduleName "wg-antidpi";
:if ([[:len [/system scheduler find name="$scheduleName"]] = 0) do={
    /log warning "[wg-antidpi] Alert : Schedule does not exist. Creating schedule ...."
    /system scheduler add name=$scheduleName interval=5m start-time=startup on-event=wg-
antidpi policy=read,write,policy,test,sniff,sensitive
    /log warning "[wg-antidpi] Alert : Schedule created!"
}

# MAIN PART
:global Tx
:global Rx
/interface wireguard peers
:foreach i in=[find where disabled=no and responder!=yes] do={
    :local LocalTx [get $i tx]
    :local LocalRx [get $i rx]
    :local LastHandshake [get $i last-handshake]
    :if ((([:tostr $LastHandshake] = "") or (($LastHandshake > [:totime "2m20s"])) and ($Rx-
>[:tostr $i] = $LocalRx))) do={
        :local PeerName [get $i name]
        :local Interface [get $i interface]
        :local EndpointAddress [get $i endpoint-address]
```

```

:local EndpointIP [get $i current-endpoint-address]
:local DstPort [get $i current-endpoint-port]
:local RawHeader [:rndstr length=4 from=123456789abcdef]

#Reset source port
/interface wireguard set $Interface listen-port=0
:local SrcPort [/interface wireguard get $Interface listen-port]

#Log peer info
:log warning ("Peer: $PeerName, Interface: $Interface")
:log warning ("Endpoint Address: $EndpointAddress, Endpoint IP: $EndpointIP")
:log warning ("Src Port: $SrcPort, Dst Port: $DstPort, Last Handshake:
$LastHandshake")
:log warning ("Last Rx: " . $Rx->[:tostr $i] . ", Current Rx: $LocalRx")
:log warning ("Last Tx: " . $Tx->[:tostr $i] . ", Current Tx: $LocalTx")

#Disable peer
:log warning ("Disable peer: $PeerName")
set $i disabled=yes
:delay 1

#Generating spam
:log warning ("Generating spam")
/tool traffic-generator stream remove [find]
/tool traffic-generator packet-template remove [find]
:delay 1
/tool traffic-generator packet-template add header-stack=mac,ip,udp,raw ip-
dst=$EndpointIP name=packet-template-wg raw-header=$RawHeader special-footer=no udp-dst-
port=$DstPort udp-src-port=$SrcPort
:delay 1
/tool traffic-generator stream add disabled=no mbps=1 name=stream1 id=3 packet-
size=1450 pps=0 tx-template=packet-template-wg
:delay 1
/tool traffic-generator quick duration=4

#Enable peer
:log warning ("Enable peer: $PeerName")
set $i disabled=no
}

:set ($Tx->[:tostr $i]) $LocalTx
:set ($Rx->[:tostr $i]) $LocalRx

```

}

Revision #1

Created 10 December 2025 09:48:45 by Admin

Updated 10 December 2025 09:50:32 by Admin